



**THE ORIGINAL EXTENDED WEAR LIFE FABRIC!**

**SPECIFICATION SHEET FOR BANWEAR style BW900-T**

<b>FABRIC:</b>	<b>BANWEAR® STYLE BW900-T 88% COTTON / 12% NYLON TWILL</b>
<b>WIDTH:</b>	<b>60/61"</b>
<b>THREAD COUNT:</b>	<b>94 X 50 THREADS PER SQUARE INCH</b>
<b>WEIGHT:</b> (ASTM D3776-96)	<b>9.0 oz. PER SQ. YARD (Minimum)</b>
<b>BREAKING STRENGTH:</b> (ASTM D5034)	<b>130 lbs. WARP (Minimum) 100 lbs. FILL (Minimum)</b>
<b>TEARING STRENGTH:</b> (ASTM D1424)	<b>7.0 x 7.0 lbs. (Minimum)</b>
<b>SHRINKAGE:</b> (AATCC 96-1997)	<b>5.0% MAXIMUM WARP &amp; FILL OVER THE LIFE OF THE GARMENT</b>
<b>FLAMMABILITY:</b>	<b>FEDERAL TEST METHOD 191 STANDARD METHOD 5903.1</b>
<b>AFTER FLAME:</b>	<b>2.0 SECONDS (Initial) 2.0 SECONDS (After 3 Launderings)</b>
<b>CHAR LENGTH:</b>	<b>4.0 INCHES (Maximum)</b>
<b>CARE INSTRUCTIONS:</b>	<b>MACHINE WASH HOT WITH DETERGENT NO CHLORINE BLEACH - NO SOAP TUMBLE DRY WARM DRY CLEANABLE</b>

**THIS FABRIC MEETS THE INDUSTRY STANDARDS AS OUTLINED IN  
ASTM F1506, NFPA70E HRC/2, NFPA1975, NFPA2112, and OSHA 29 CFR 1910.269**

***PROVIDED THE CARE INSTRUCTIONS ARE PROPERLY FOLLOWED, THE FINISH IN THIS FABRIC IS  
DESIGNED TO LAST THE USABLE LIFE OF THE GARMENT***